



315 S Black Cat Rd
Joplin, MO 64801
417-437-6985

www.newmansrestoration.com



*Restrictions Apply

X90

X90 is a second step in the Anabec System of Products. Application of X90 results in an extremely durable moisture barrier. X90 is applied after cleaning the surface with Advanced Cleaning Solution. This product is appropriate for use on previously cleaned and/or disinfected, unfinished building material surfaces. X90 can serve as a primer for latex paints.

X90

General Characteristics:

- Ready to Use
- Surface Penetrant

Color:

- Solid White

Coverage:

- 250-400 sq ft / gallon

Choose the **Anabec System** Better Chemistry. Superior Results.

x90

Product Info

Classification
Key Ingredient(s)

Moisture Barrier
Acrylic
Silver

Packaging / Storage

| | |
|--------------------|--|
| Packaged | 5 gal bucket |
| Shelf Life | 18 months |
| Storage Conditions | Do not Freeze Store out of reach of children |

Properties

| | |
|----------------------|-----------------|
| Finish after applied | Solid-White |
| Odor | None |
| pH | 6.5-8.5 |
| Viscosity | 2,000-3,000 cps |
| Density | 10.2 lbs/gal |
| Flash Point | >100 C |
| Est VOC | 0.43 lbs /gal |
| Solubility in Water | Soluble |

Application

| | |
|------------------|--------------------|
| Dilution | Ready to Use |
| Coverage | 250-400 sq ft /gal |
| Air Less Sprayer | Yes |
| Brush | Yes |
| Roller | Yes |
| Reoccupy Space | 30 mins |
| Dry to touch | 2 hours |
| Dry through | 18-24 hours |
| Clean-up | Water / Soap |



315 S Black Cat Rd
Joplin, MO 64801
417-437-6985

www.newmansrestoration.com